

Low Row-HM12A

|                                       |                                                                                                                           |                |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------|----------------|
| 1: Main Frame Gauge Tube 50*110*2.0mm | Flat Oval Tube 50*100*2.5mm; Shroud Frame Rectangular                                                                     |                |
| 2: Wire Spec.                         | Dia 5.6mm                                                                                                                 |                |
| 3: Cushion                            | Material: High strength sponge, artificial PVC leather                                                                    |                |
| 4: Guiding Bar                        | Round 20*2.0mm Stainless Steel Bar                                                                                        |                |
| 5: Shroud Cover                       | Integrated iron guard plate makes the equipment safe, beautiful and seamless                                              |                |
| 6: Handle                             | Embossed spraying process                                                                                                 |                |
| 7: Adjusting Position                 | Fixed and not adjustable                                                                                                  |                |
| 8: Weight Stack                       | Steel plate thickness : 18mm; Better impact and wear resistance; Standard configuration: 80kgx1 group, 5kg/piece          |                |
| 9: Pulleys                            | High Strength Nylon Pulleys, which have passed the over 100,000 times non-stop fatigue tests                              |                |
| 10: Accessories                       | High strength bolts and locknuts, which can meet National Standard Grade 8.8, are better in strength and rust resistance. |                |
| 11: Size/ N.W.                        | Size: 1753*1154*1901mm (L*W*H)                                                                                            |                |
| 12: Size/ N.W.                        |                                                                                                                           |                |
| 13: Manual                            | Chinese Manual                                                                                                            | English Manual |
| 14: Muscles Trained                   | Exercise the latissimus dorsi.                                                                                            |                |